


Amendments to the Claims

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims

1. (Previously presented) An electroluminescent element comprising:
a pair of electrodes; and
an electroluminescent layer comprising a host material and a guest material and provided between said pair of electrodes,
wherein each of said host material and said guest material is a compound having a skeleton represented by the general formula 1:

Formula 1



wherein, in the guest material:

R₁ is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and

R₂ to R₅, each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a

heterocyclic group which may have a substituent, and Ar₁ is an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and wherein, in the host material:

R₁ is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent,

three of R₂ to R₅, each of which may be the same or different, are individually a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and Ar₁ is an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and

one of R₂ to R₅ is a hydrogen atom.


2. (Previously presented) An electroluminescent element comprising:

a pair of electrodes; and

an electroluminescent layer comprising a host material and a guest material and provided between said pair of electrodes,


wherein said host material is a compound having a skeleton represented by the general formula 2:

Formula 2



wherein said guest material is a compound having a skeleton represented by the general formula 3:


Formula 3



wherein R₁ is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and R₂ to R₅, each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent,

wherein at least one substituent out of substituents X₁ to X₆ represented by the general formula 2 and a substituent X₁ represented by the general formula 3 have an imidazole skeleton represented by the general formula 4:

Formula 4



wherein, in the guest material:

R_1 is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and

R_2 to R_5 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and
wherein, in the host material:

R_1 is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent,

three of R_2 to R_5 , each of which may be the same or different, are individually a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and


one of R_2 to R_5 is a hydrogen atom.

3. (Previously presented) An electroluminescent element comprising:
a pair of electrodes; and

an electroluminescent layer comprising a host material and a guest material and provided between said pair of electrodes,

wherein said host material is a compound represented by the general formula 5:

Formula 5




wherein R₁ is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent,

wherein three of R₂ to R₅, each of which may be the same or different, are individually a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent,

wherein one of R₂ to R₅ is a hydrogen atom, and

wherein said guest material is a compound represented by the general formula 6:

Formula 6



wherein R_1 is a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, R_2 to R_9 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and R_{10} and R_{11} are individually a hydrogen atom, a lower alkyl group, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and

wherein R_8 and R_{10} , and R_9 and R_{11} , may be bonded each other to form a substituted or nonsubstituted saturated six-membered ring.


4. (Cancelled)

5. (Withdrawn) An electroluminescent element comprising:

a pair of electrodes; and

host materials and guest materials provided between said electrodes and having in their molecule skeletons represented by the general formula 9:

Formula 9




wherein X_1 to X_4 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group

which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent.

6. (Withdrawn) An electroluminescent element comprising: a pair of electrodes;
a compound provided between said electrodes as host materials represented by the
general formula:


Formula 10



wherein Ar₁ and Ar₂, each of which may be the same or different, are individually an aryl group which may have a substituent, or a heterocyclic group which may have a substituent, and R₁ and R₂, each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent;

and a compound provided between said electrodes as guest materials represented by the
general formula 11:


Formula 11



wherein R_1 to R_8 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent.

7. (Withdrawn) An electroluminescent element comprising:
 a pair of electrodes;
 a compound provided between said electrodes as host materials represented by the general formula 12:

Formula 12




wherein R_1 and R_2 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro

group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent;

and a compound provided between said electrodes as guest materials represented by the general formula 13:


Formula 13



wherein R_1 to R_8 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent.

8. (Currently amended) An electroluminescent element comprising:
 a pair of electrodes; and
an electroluminescent layer provided between said pair of electrodes, the electroluminescent layer comprising a host material materials and a guest material, materials wherein each of said host material and said guest material is a compound having a skeleton having in their molecule skeletons represented by the general formula 14:

Formula 14



wherein X_1 to X_3 , each of which may be the same or different, are individually a hydrogen atom, a halogen atom, a lower alkyl group, an alkoxy group, an acyl group, a nitro group, a cyano group, an amino group, a dialkylamino group, a diarylamino group, a vinyl group which may have a substituent, an aryl group which may have a substituent, or a heterocyclic group which may have a substituent.

9. (Previously presented) An electroluminescent element according to claim 3 wherein said electroluminescent element is incorporated into one selected from the group consisting of a display device, a computer, an image reproduction device including a recording medium, a goggle type display, a camera, and a cellular phone.

10. (Previously presented) An electroluminescent element according to claim 3 wherein one of said electrodes is an anode.

11. (Previously Presented) An electroluminescent element according to claim 10 wherein said anode comprises a material selected from the group consisting of indium tin oxide, indium zinc oxide composed of indium oxide mixed with zinc oxide, aurum, platinum, nickel, tungsten, chrome, molybdenum, ferrum, cobalt, copper, palladium, and nitride of metal material.

12. (Previously presented) An electroluminescent element according to claim 3 wherein the other of said electrodes is a cathode.

13. (Previously Presented) An electroluminescent element according to claim 12 wherein said cathode comprises a material selected from the group consisting of alkaline metal, alkaline earth metal, alloy thereof, and compound thereof.

14. (Previously Presented) An electroluminescent element according to claim 12 wherein said cathode comprises a material selected from the group consisting of Li, Cs, Mg, Ca, Sr, Mg:Ag, Al:Li, LiF, CsF and CaF₂.

15. (Previously presented) An electroluminescent element according to claim 3 wherein each of said electrodes has a thickness of 10 to 500 nm.

16. (Previously presented) An electroluminescent element according to claim 3 wherein at least one of said electrodes comprises a material having light transmission properties.

17. (Previously presented) An electroluminescent element according to claim 3 wherein said compound provided between said electrodes as said host materials is provided in a light-emitting layer, and wherein said compound provided between said electrodes as said guest materials is provided in said light-emitting layer.

18. (Previously presented) An electroluminescent element according to claim 3 further comprising an electron transporting layer provided between said electrodes.

19. (Previously presented) An electroluminescent element according to claim 3 further comprising a hole injecting layer provided between said electrodes.

20. (Previously presented) An electroluminescent element according to claim 3 further comprising a hole blocking layer provided between said electrodes.

21. (Previously Presented) An electroluminescent element according to claim 17 wherein said light-emitting layer is provided over one of said electrodes which is an anode, and wherein the other of said electrodes which is a cathode is provided over said light-emitting layer.

22. (Previously Presented) An electroluminescent element according to claim 17 wherein said light-emitting layer is provided over one of said electrodes which is a cathode, and wherein the other of said electrodes which is an anode is provided over said light emitting layer.

23. (Previously Presented) An electroluminescent element according to claim 17 further comprising an electron transporting layer provided over said light-emitting layer wherein said light-emitting layer is provided over one of said electrodes which is an anode, and wherein the other of said electrodes which is a cathode is provided over said electron transporting layer.

24. (Previously Presented) An electroluminescent element according to claim 17 further comprising a hole injecting layer provided over one of said electrodes which is an anode wherein said light-emitting layer is provided over said hole injecting layer, and wherein the other of said electrodes which is a cathode is provided over said light-emitting layer.

25. (Previously Presented) A light-emitting device comprising the electroluminescent element according to claim 1 in a pixel portion.

26. (Previously Presented) A light-emitting device comprising the electroluminescent element according to claim 2 in a pixel portion.

27. (Previously Presented) A light-emitting device comprising the electroluminescent element according to claim 3 in a pixel portion.

28-32. (Cancelled)